



Stainless steel case dry pressure gauges, parts in contact with the process in brass material, sensing element Bourdon tube, suitable for applications with non aggressive fluids or gases to the copper alloy. Fit properly in outdoor installation.

P-Type local mounting, back connection



R-Type direct local mounting, radial connection



| Dimensions: mm | A | C | D | d | F | H | I | K | L | M | T | Ch | Weight |
|----------------|----|----|----|---|---|---------|---|---|---------|---|---------|----|--------|
| P-Type | 27 | 10 | 51 | | 1/8 M/F BSP, BSPT, NPT 1/4 BSP, NPT, PG7 | 43 / 47 | | | 10 / 13 | | max 20 | 14 | |
| R-Type | 27 | 10 | 51 | | 1/8-1/4 BSP, 1/8 NPT | 67 / 71 | | | 10 / 13 | | 16 / 20 | 14 | |

Technical features

Reference standard: EN 837-1.

Pressure ranges: from -1 bar to 600 bar.

Accuracy: Kl. 2,5 % according to EN 837-1.

Ambient temperature: -25 ...+65 °C.

Process fluid temperature: +0 ...+65 °C.

Thermal effect: When working temperature deviates from reference temperature (+ 20°C): max ± 0,4 % / 10K of end-of-scale value.

Working pressure: Steady: 3/4 full scale value.
Fluctuating: 2/3 full scale value.
Short time: full scale value.

Ingress protection: IP 65 according to EN 60 529 / IEC 529.

Design features

Process connection: Cu alloy.

Cu alloy Bourdon tube: C-type < 60 bar;
helical-type ≥ 60 bar.

Case / Bezel ring: stainless steel.

Window: plastic material SAN.

Movement: Cu alloy.

Dial: aluminium white with standard black / red lettering.

Pointer: polyamide PA66 30% GF black.

Options

Window transparent safety glass.

Average working temperature increased till 100 °C with special soft soldering.

Accuracy Kl. 1,6 %.

Nickel-plated process connection.

Damping treatment.

Threads on request obtainable from Ø14.

Internal pressure restrictor.

Ordering Informations:

Type / Nominal Diameter / Pressure Range / Connection Type / Options

Modifications may take place and materials specified may be replaced by others without prior notice.
Specifications and dimensions given in this leaflet represent the state of engineering at the time of printing.